



Typ	a=4/1		Wymiary (mm)																						
	Wysokość podnoszenia	Udźwig	Prędkość podnoszenia /m/min/				L2	L3	L4	L5	L6	B1	B2	B3	B4	H1	H2	e	d	d1	d2				
			4	6	4/1	6/1																			
			L1																						
VAT10	H1	6.5	2000	1035	1035	1072	1072	296	28	534	-6	123	320	240	40	45	450	295	17	8	M16	016			
	H2	9	1255	1255	1292	1292	406	754															-60	233	
	H3	12	1475	1475	1512	1512	516	974															-96	343	
VAT20	H1	7.5	4000	1153	1153	1200	1200	324	41.5	565	25	132	430	325	52.5	50	540	355	1.5	10	M20	022			
	H2	11	1373	1373	1420	1420	434	785															-30	242	
	H3	14.5	1593	1593	1640	1640	544	1005															-85	352	
VAT30	H1	6.5	6300	1167	1196	1190	1190	324	41.5	565	30	76	430	325	52.5	56	565	355	1.5	12	M20	022			
	H2	9.5	1387	1416	1410	1410	434	785															-25	186	
	H3	12.5	1607	1636	1630	1630	544	1005															-80	296	
VAT40	H1	6	10000	1206	1232	1287	1287	312	36	550	50	42	480	370	55	71	775	395	2	14	M24	026			
	H2	9		1452	1478	1533	1533	435															796	-10	165
	H3	12		1698	1724	1779	1779	558															1042	-70	288
	H4	15		1917	1943	1838	1838	668															1261	-105	398
VAT50	H1	6	20000	1436	1436	1436	1436	330	40	575	55	52	620	520	50	90	980	455	26	18	M33	026			
	H2	9		1636	1636	1636	1636	430															775	5	152
	H3	12		1836	1836	1836	1836	530															975	-45	252
	H4	18		2236	2236	2236	2236	730															1375	-90	452

Typ	a=4/1		Wymiary (mm)																			
	Wysokość podnoszenia (mm)	Udźwig	Prędkość podnoszenia /m/min/				L2	L3	L4	L5	L6	B1	B2	B3	B4	H1	H2	e	d	d1	d2	
			2.5	4	2.5/0.6	4/0.6																
			L1																			
VAT60	H1	7	25000	1600	1600	1600	1600	394	68	650	91	40	800	660	70	100	1100	535	29	20	M33	033
	H2	8.5		1660	1660	1660	1660	444		750	116	90										
	H3	11.5		1870	1870	1870	1870	549		960	169	195										
	H4	14.5		2080	2080	2080	2080	654		1170	221	300										
	H5	17.5		2290	2290	2290	2290	759		1380	273	355										
	H6	20.5		2500	2500	2500	2500	864		1590	326	410										
	H7	23.5		2710	2710	2710	2710	969		1800	378	465										
VAT64	H1	5.5	32000	1600	1600	1600	1600	394	68	650	91	40	800	660	70	100	1100	535	29	24	M33	033
	H2	7		1660	1660	1660	1660	444		750	116	90										
	H3	9.5		1870	1870	1870	1870	549		960	169	195										
	H4	12		2080	2080	2080	2080	654		1170	221	300										
	H5	14.5		2290	2290	2290	2290	759		1380	273	355										
	H6	17		2500	2500	2500	2500	864		1590	326	410										
	H7	20		2710	2710	2710	2710	969		1800	378	465										

Typ	a=4/1		Wymiary (mm)																			
	Wysokość podnoszenia (mm)	Udźwig	Prędkość podnoszenia /m/min/				L2	L3	L4	L5	L6	B1	B2	B3	B4	H1	H2	e	d	d1	d2	
			4	6	4/1	6/1																
			L1																			
VATB64	H1	7	25000	1600	1600	1600	1600	394	68	650	91	40	800	660	70	100	1100	535	29	20	M33	033
	H2	8.5		1660	1660	1660	1660	444		750	116	90										
	H3	11.5		1870	1870	1870	1870	549		960	169	195										
	H4	14.5		2080	2080	2080	2080	654		1170	221	300										
	H5	17.5		2290	2290	2290	2290	759		1380	273	355										
	H6	20.5		2500	2500	2500	2500	864		1590	326	410										
	H7	23.5		2710	2710	2710	2710	969		1800	378	465										