








Typ	083118	083112	083115	083116	083117
Prąd znamionowy [A]	10	32	60	100	125
Opór poziomy [Ω /m]	0,029314	0,005507	0,001185	0,000750	0,000548
Materiał	Datametall	stal	miedź		

Rodzaj systemu	Szynoprzew. skrzynek.	Szynoprzew. kompakt.	Szynoprzewody jednobiegunowe izolowane			
Program	842	831	815	811	812	813
						
Prąd znamionowy ¹⁾ [A]	35 -140 ³⁾	10-125 ⁴⁾	100	10-100	25-400	200-1250
Nap. znamionowe [V]	600	500	500	500	660	660
Odstępy montaż. [m]	2	1	0,5	0,4-1,0	1,5	2,5
Długość szyny ²⁾ [mm]	4000	4000	4000	4000	4000	5000
Wymiary zewnętrzne [mm]	5-bieg: 7-bieg: 56 x 90	3-bieg: 26 x 62 4-bieg: 26 x 80 5-bieg: 26 x 98	9,6 x 15,2	14,7 x 15,5	18 x 26	32 x 42
1) przy 100% ED i 35°C; 2) standardowa długość szyn; 3) 160 A przy 80% ED; 3) 140 A przy 80% ED						