

YALE lift ITP./ LHP

Model	Nośność	Liczba ciągów	Rozmiar	Szerokość belki jezdnej mm	Grubość dolnej półki t max. mm	Minimalny promień skrętu m	Waga w kg przy 3 m z blokiem			
							-P	-G	-P	-G
Yalelift IT	500	1	A	50-180	19	0,90	20	24	26	31
	500	1	B	180-300	19	0,90	21	25	27	32
	1000	1	A	50-180	19	0,90	27	32	35	40
	1000	1	B	180-300	19	0,90	29	33	37	41
	2000	1	A	58-180	19	1,15	44	49	52	57
	2000	1	B	180-300	19	1,15	46	50	54	58
	3000	1	A	74-180	27	1,40	77	82	86	91
	3000	1	B	180-300	27	1,40	79	84	88	93
	5000	2	A	98-180	27	1,80	125	130	135	140
	5000	2	B	180-300	27	1,80	129	134	139	144
Yalelift LH	500	1	A	60-180	19	0,90	27	31	33	38
	500	1	B	180-300	19	0,90	27	32	34	38
	1000	1	A	70-180	19	0,90	35	40	43	48
	1000	1	B	180-300	19	0,90	36	41	44	49
	2000	1	A	82-180	19	1,15	61	65	69	73
	2000	1	B	180-300	19	1,15	62	67	70	75
	3000	1	A	100-180	19	1,40	107	112	116	121
	3000	1	B	180-300	19	1,40	109	114	118	123
	5000	2	A	110-180	27	1,80	152	157	162	167
	5000	2	B	180-300	27	1,80	156	161	166	171
	10000	3	B	125-310	40	1,80				